



PREMICOTE™ PF

REINFORCING POLYESTER FABRIC

FOR PROFESSIONAL USE ONLY

Weight	3 ounce sq. yd. 100 gram sq. meter
Thickness	0.025 inches
Tensile Strength:	57 psi
Elongation:	65 %
Burst Strength:	176 psi
Trapezoid Tear Strength	16 lbs.

Product Information

PRODUCT TYPE: Premicote PF is a stitchbonded style polyester reinforcing fabric.

GENERAL PROPERTIES: This 3 ounce stitchbond polyester is one of the strongest materials available as reinforcement in cold process roofing. It offers an unusual combination of high strength properties, delivering good elongation for excellent thermal stress force accommodations.

Available in both 4" (Premicote PF-4) and 40 inch (Premicote PF-40)

RECOMMENDED USES: Used in the reinforcement of cold process roofing. It is also used as a flashing reinforcement with mastics and elastomers. The premicote PF series Polyester Fabric has superior strength and elongation making it excellent for reinforcing seams and details in many roofing applications. Narrow width (Premicote PF-4) is suitable for seam applications in metal roof restorations and single ply restoration.

Premicote PF is a medium soft product. It will conform to smooth surfaces quite easily. Light brooming may be necessary to ensure good coating embedment and air pocket removal.

Please consult the Premium Spray Products technical department for specific application questions for this product.

COLOR: White

APPLICATION: Embed fabric in wet coating ensuring there are no fishmouths. Additional application of coating can typically be immediately applied over the embedded fabric. Coating applications should extend at least 1" beyond fabric edge.

PRODUCT IS AVAILABLE IN:

- 4" x 324' Rolls (Premicote PF-4)
- 40" x 324' Rolls Premicote PF-40)

HMIS® RATING: Health 0, Flammability 0, Reactivity 0, Protection X
(0 = Minimal, 1 = Slight, 2 = Moderate, 3 = Serious, 4 = Severe)

Premium Spray Products

At Premium Spray Products we are dedicated to providing quality products that add true value through long term performance and ease of use.

We manufacture a variety of Spray Polyurethane Foam products and protective coatings that are used in both the residential and commercial markets. Our Spray Polyurethane Foam is manufactured for a variety of uses that include residential and commercial building insulation, exterior roofing and poured in place foam for industrial applications.

All polyurethane chemical systems are not created equal. The chemistry makes a big difference. Our formulations are carefully designed to provide our customers with systems that are superior in their processing and application performance.

Homeowners, building owners and end users demand performance that includes affordability, reliability, comfort and ease of use. At Premium Spray Products, Inc. we meet these demands through a daily commitment to quality, technology, service and support for our valued customers.

To the best of our knowledge, all technical data contained herein is true and accurate as of the date of issuance and subject to change without prior notice. User must contact Premium Spray Products to verify correctness before specifying or ordering. We guarantee our products to conform to the quality control standards established by Premium Spray Products. We assume no responsibility for coverage, performance or injuries resulting from use. Liability, if any, is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY PREMIUM SPRAY PRODUCTS EXPRESSED OR IMPLIED; STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

PREMICOTE™ and Premium Spray Products are trademarks of Premium Spray Products, Inc.

PREMICOTE™ PF
REINFORCING POLYESTER FABRIC
FOR PROFESSIONAL USE ONLY

*Experience the
Premium Difference*

Your Local Authorized Contractor



1255 Kennestone Circle, #200 · Marietta, Georgia 30066

Phone: 770.528.9556
www.PremiumSpray.com