



# PREMICOTE™ P75

## PRIMER COATING

FOR PROFESSIONAL USE ONLY

PHYSICAL PROPERTY	TYPICAL VALUE	ASTM TEST METHOD
<b>Solids Content By Weight:</b>	1.30%	ASTM D-1353
<b>Solids Content By Volume:</b>	25%	ASTM D-2697
<b>Flash Point:</b>	None to 212°F	ASTM D-1310
<b>Cure Time:</b>	Dry to touch in 1-2 hours, full cure in 12 hours. Drying time is temperature, humidity, and film thickness dependent.	
<b>Clean up</b>	Use water	
<b>Maximum Continuous Service Temperature</b>	185 °F (85 °C)	
<b>Shelf Life:</b>	(UNOPENED CONTAINERS): 6 months when stored between 35°F and 75°F	
<b>VOC:</b>	< 50 Grams / Liter	

### Product Information

**GENERAL PROPERTIES:** This product is designed to perform as an intermediate barrier that provides outstanding adhesion, excellent flexibility and toughness to a variety of substrates.

**RECOMMENDED USES:** This primer is suitable when a fast-drying, primer is needed. This product may be used on many surfaces for effective protection: BUR, Wood, Metal, Concrete (minimum 30 day cured), Polyurethane Foam, and Masonry.

**PRODUCT LIMITATIONS:** Do not apply when it is raining or if the threat of rain exists. Also, do not apply when the dew point is less than 5°F above ambient temperature. Subsequent coats should be applied within 48 hours of prior applications to insure full and uniform adhesion. Do not use on new concrete (less than 30 days).

Please consult the Premium Spray Products Technical Department for any specific questions regarding the application of this product.

### Standard Colors

**PRODUCT IS AVAILABLE IN:** Black

Special colors available upon request at an additional charge. Allow additional manufacturing time for non-standard colors.

### Ordering Information

**PRODUCT IS AVAILABLE IN:**

- 5 Gallon Pails (19 liters)
- 55 Gallon Drums (209 liters)

**SHIPPING INFORMATION:**

Container Size	Class Rating
5 Gallon (45lbs.)	55
55 Gallon (495lbs.)	55

**D.O.T. CLASSIFICATION:** Roof Coating – Not Regulated

**HMIS® RATING:** Health 1, Flammability 0, Reactivity 0, Protection X  
0 = Minimal 1 = Slight 2 = Moderate 4 = Serious

### Premium Spray Products

At Premium Spray Products we are dedicated to providing quality products that add true value through long term performance and ease of use.

We manufacture a variety of Spray Polyurethane Foam products and protective coatings that are used in both the residential and commercial markets. Our Spray Polyurethane Foam is manufactured for a variety of uses that include residential and commercial building insulation, exterior roofing and poured in place foam for industrial applications.

All polyurethane chemical systems are not created equal. The chemistry makes a big difference. Our formulations are carefully designed to provide our customers with systems that are superior in their processing and application performance.

Homeowners, building owners and end users demand performance that includes affordability, reliability, comfort and ease of use. At Premium Spray Products, Inc. we meet these demands through a daily commitment to quality, technology, service and support for our valued customers.



To the best of our knowledge, all technical data contained herein is true and accurate as of the date of issuance and subject to change without prior notice. User must contact Premium Spray Products to verify correctness before specifying or ordering. We guarantee our products to conform to the quality control standards established by Premium Spray Products. We assume no responsibility for coverage, performance or injuries resulting from use. Liability, if any, is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY PREMIUM SPRAY PRODUCTS EXPRESSED OR IMPLIED; STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

PREMICOTE™ and Premium Spray Products are trademarks of Premium Spray Products, Inc.

# PREMICOTE™ P75

PRIMER COATING  
FOR PROFESSIONAL USE ONLY

Experience the  
Premium Difference

## Application Instructions

### Application Procedures

**DO NOT THIN.**

**SURFACE PREPARATION:** All surfaces to be primed must be clean, dry, and paintable. It may be necessary to power wash to enhance adhesion. See application specification for more details.

**MIXING PROCEDURES:** Product may separate after shipping and storage, though it may still look mixed. For best results, thoroughly blend contents of all containers using a power mixer for a minimum of 10 minutes prior to use.

**WEATHER RESTRICTIONS:** It is very important that this product is not used when weather conditions are below 50° F., or when there is a chance that temperatures could fall below 32°F. within a 24 hour period after application. We also do not recommend application of this product if rain or dew is likely to occur before curing of product.

**APPLICATION RATES:** Substrates should be coated until it appears wet. Care should be taken not to flood or over apply primer. Yield is 150 to 300 square feet per gallon, depending on the porosity of the substrate.

**APPLICATION EQUIPMENT:** This product may be sprayed, brushed, or rolled. Low-pressure airless spray equipment can be used to apply this material.

**APPLICATION PROCEDURES:** This product may be applied directly to any clean, dry surface. Subsequent coats should be applied within 48 hours of prior applications to insure full and uniform adhesion.

Before applying a subsequent coat, the previous coat must be completely dry and cured. If any contamination of a thoroughly cured surface occurs, it must be washed with a chemical cleaner before applying subsequent coats. Coating must be extended beyond the substrate to create a self-terminating flashing. Consult Manufacturer for recommended dry film thickness.

**SAFETY PRECAUTIONS:** Installers should use caution during spray processes to avoid falls caused by slipping on wet primer. Installers should read and understand all technical and informational literature on this product, including the Material Safety Data Sheet, prior to using this product.

Your Local Authorized Contractor



1255 Kennestone Circle, #200 · Marietta, Georgia 30066

Phone: 770.528.9556

[www.PremiumSpray.com](http://www.PremiumSpray.com)