



# PREMICOTE™ P-79

## RUST INHIBITIVE PRIMER

FOR PROFESSIONAL USE ONLY

PHYSICAL PROPERTY	TYPICAL VALUE
Total Solids	40% ± 2%
Weight Per Gallon	10.1 lbs per gallon ± 0.2
VOC	62 g/liter
Clean Up	Water
Shelf Life	12 months @ 40°-90°F
Color	Red
Viscosity	900 ± 200 cP

### Premium Spray Products

At Premium Spray Products we are dedicated to providing quality products that add true value through long term performance and ease of use.

We manufacture a variety of Spray Polyurethane Foam products and protective coatings that are used in both the residential and commercial markets. Our Spray Polyurethane Foam is manufactured for a variety of uses that include residential and commercial building insulation, exterior roofing and poured in place foam for industrial applications.

All polyurethane chemical systems are not created equal. The chemistry makes a big difference. Our formulations are carefully designed to provide our customers with systems that are superior in their processing and application performance.

Homeowners, building owners and end users demand performance that includes affordability, reliability, comfort and ease of use. At Premium Spray Products, Inc. we meet these demands through a daily commitment to quality, technology, service and support for our valued customers.

### Product Information

**DESCRIPTION:** **PREMICOTE™ P-79** is a water-based, rust inhibiting, low VOC primer developed to be used to protect metal substrates. P-79 is based on self crosslinking technologies that allow for low VOC levels along with greater corrosion resistance and adhesion properties. Premicote P-79 has excellent resistance to heat, cold, moisture and weathering. This primer dries quickly allowing for reduced time before elastomeric coating application.

**RECOMMENDED USES:** **PREMICOTE™ P-79** may be used as a prime coat over primarily metal surfaces but can be also be applied to a wide range of substrates which include, but are not limited to, wood, metal, concrete, masonry, various single ply membranes, spray polyurethane foam and most commonly used roof coatings. The dark red color speeds up drying and increases roof surface temperature before application of roof coatings. Low VOC levels allow for application in most air quality restrictive areas around the country.

**LIMITATIONS AND PRECAUTIONS:** **PREMICOTE™ P-79** is a water based primer and is not freeze-thaw stable. It will freeze and become unusable at temperatures below 32°F. PROTECT FROM FREEZING DURING SHIPMENT AND STORAGE. Do not store material at temperatures below 45° F. Do not apply Premicote P-79 when ambient air and substrate temperatures fall below 45° F, or when inclement weather is forecast. Apply next coating as soon as possible after primer cures.

**PONDING WATER:** Premium Spray Products, Inc., warranties do not cover damage due to ponding water.

The National Roofing Contractors Association considers ponding water on any roof unacceptable. (See the NRCA Roofing and Waterproofing Manual).

### Standard Colors

**FINISH:** Red

### Ordering Information

#### PRODUCT IS AVAILABLE IN:

- 5 Gallon Pails (18.9 Liters)
- 55 Gallon Drums containing 55 Gallons of material (208.2 Liters)

#### SHIPPING INFORMATION:

Container Size	Class Rating
5 Gallon	55
55 Gallon	55

**D.O.T. CLASSIFICATION:** Roof Coating – Not Regulated

**HMSIS® RATING:** Health 1, Flammability 0, Reactivity 0, Protection X  
0= Minimal 1=Slight 2=Moderate 3=Serious 4=Severe

# PREMICOTE™ P-79

**RUST INHIBITIVE PRIMER**  
FOR PROFESSIONAL USE ONLY

*Experience the  
Premium Difference*

## *Application Instructions*

Medium nap rollers or conventional airless spray equipment may be used to apply Premicote P-79. Apply Premicote P-79 only to clean, dry surfaces free of loose particles or other foreign matter. Pressure washing is required on metal surfaces showing signs of oxidation. Apply Premicote P-79 at the rate of 1 gallon per 200 sq. ft., according to substrate and condition. Normal drying time is 2-3 hours. PRODUCT APPLICATION SHOULD BE SUSPENDED AND OUR TECHNICAL SERVICE PERSONNEL CONTACTED IF THE RESULTS OBTAINED ARE LESS THAN DESIRABLE.

*Your Local Authorized Contractor*



1255 Kennestone Circle, #200 · Marietta, Georgia 30066

Phone: 770.528.9556

[www.PremiumSpray.com](http://www.PremiumSpray.com)